





# Facings for U SeaProtect insulation products

Glass filament fabric, white coloured.



## MECHANICAL RESISTANCE

Strong mechanical protection of the wool.

### EASY Polls

# EASY HANDLING

Rolls in handable delivery form that can be carried by one person (< 20 kg). Can be cleaned by wiping or gentle washing.



## SOUND ABSORPTION

Excellent absorption properties when combined with mineral wool substrate.







		r			
CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD	
Reaction to fire	-	-	Low Frame Spread according to IMO Certificate Nr.: 118.168	IMO-Resolution MSC.61(67)-(FT- PCode), IMO MSC/Circ.1120	
Application field	-	-	Facing of mineral wool products	-	
Material	-	-	E-glass filaments woven fabric, white coloured, low flame spread surface material, consistent structure, non-slipping filaments, fibers with a diameter of ≤ 3 µm can not be contained	-	
Texture weave	-	-	Linen	DIN 61101/1+2	
Gramweight	-	[g/m²]	210 - 220 ± 5 %	DIN EN 12127	
Tensile strength warp	-	[N/50 mm]	≥ 1500	ISO 4606	
Tensile strength weft	-	[N/50 mm]	≥ 900	ISO 4606	
Type approval certificates			EC-Type Examination MED-B (Low Flame Spread): 118168-04 exp. 22/10/2028 QAS MED-D Certificate: SEE0736Q0000108 exp. 19/05/2027		
DELIVERY FORM: STANDARD DIMENSIONS / PACKAGING INFORMATION*					

LENGTH [M]	WIDTH B [M]	DIAMETER Ø [M]	WEIGTH PER ROLL [KG]			
55	1.25	0.2	19			

\* Dimensions on request, products with minimum order quantities are requested



#### www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our lsover sales offices. We deliver only according to our terms of trade and terms of delivery.

SAINT-GOBAIN ISOVER · Tour Saint-Gobain 12 place de l'Iris 92096 La Défense cedex - France

