



U Protect Wi- red Mat 4.0 Alu1

U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

U Protect WM 4.0 is part of ISOVER solutions for providing fire resistance in HVAC applications by using high performing ULTIMATE mineral wool.

U Protect wired mats provide fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for circular and rectangular ventilation and smoke extraction ducts up to EI 120.

Installation guidelines must be followed and all ISOVER U Protect components used.



THERMAL INSULATION

High class insulation keeps the medium temperature as designed and secures system operating with minimal losses



FIRE RESISTANCE

Passive fire protection system



SOUND INSULATION

The ability of mineral wool to act as a spring results in reducing vibration and noise emissions in industrial processes



FAST INSTALLATION

Thanks to its light weight and high flexibility, it can be installed by one person without any special equipment

U Protect Wired Mat 4.0 Alu1



CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES									STANDARD
Thermal conductivity	T	[°C]	10	50	100	150	200	300	400	500	600	EN 12667
	λ	[W/(m·K)]	0.033	0.037	0.043	0.049	0.057	0.073	0.093	0,117	0,146	
Thermal behaviour	T	[°C]	< 400 °C (tape and alu-facing 80 °C)									EN 14706
Melting point			> 1,000 °C									-

CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD
Acoustics	α_w	-	Weighted sound absorption coefficient = 0.90	EN 11654
	-	kPa·S/m ³	Specific airflow resistance Afr = 60 (measured without facing)	EN 29053

CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD
Reaction to fire	-	-	Non-combustible, Euroclass A1	EN 13501-1
Water behaviour	-	-	Hydrophobic	EN 12086
Chemical behaviour	-	-	Silicone-free, Sulphide-free	AGI Q 132
Application field	-	-	U Protect Wired Mats offer fire-resistant insulation for HVAC systems. It's lightweight, easy to install, and provide efficient thermo-acoustic insulation for circular and rectangular ducts up to EI 120.	EN 1366-1 EN 1366-8
CE marking	-	-	MW-EN14303-T2-ST(+)400-MV2	EN 14303
Instructions for use	-	-	Installation guidelines must be followed and Protect BSF and BSK must be used to achieve the performance.	-
Quality management	-	-	ISOVER is certified according to EN ISO 9001 and EN ISO 14001	EN ISO 9001 EN ISO 14001

DELIVERY FORM: STANDARD DIMENSIONS / PACKAGING INFORMATION*

THICKNESS D [MM]	WIDTH B [MM]	LENGTH [MM]	M ² /PALLET	M ² /PACK
30	600	10,000	216.00	12.00
40		7,500	162.00	9.00
50		6,000	129.60	7.20
60		5,000	108.00	6.00
70		4,300	92.90	5.16
75		4,000	86.40	4.80
80		3,700	79.90	4.44
90		3,300	71.28	3.96
100		3,000	64.80	3.60
120		2,500	54.00	3.00

* Check availability and delivery details from your local Isover supplier. 125 mm must be installed in 2 layers 75 mm + 50 mm. U Protect Wired Mats are always loaded with 1000 Pa (i.e. approx. 100 kg/m²) when the thickness is determined, which means that the prescribed thickness is maintained.



www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our Isover sales offices. We deliver only according to our terms of trade and terms of delivery.

SAINT-GOBAIN ISOVER · Tour Saint-Gobain 12 place de l'Iris 92096 La Défense cedex - France

APR-2026

